

PF5700SG Specification Sheet



Specification:

Steel constructed swinging gate

Material:

Mild steel squared hollow section

Construction:

(standard version)

Gates - 60 x 60 x 3mm

Posts - 100 x 100 x 4mm

(heavy duty version)

Crossbeam - 80 x 80 x 5mm

Posts - 150 x 150 x 5mm

Available spans:

(single leaf version)

From 2.0 metres to 6.0 metres

(double leaf version)

From 6.0 metres to 12.0 metres

Finish:

Powder coated or galvanised as standard

Installation:

Post may be either sunken or surface mounted

Fittings:

Comes complete with padlocks and fixings

Vinyl striping is also available



The PF5700SG Manual Swinging Gate

The PF5700 swinging gate provides an ideal low cost solution to a wide variety of parking, road access and traffic management requirements.

It is ideal for locations or situations where a fully automated barrier or gate entry system is either not necessary or cost effective.

The PF5700 is available as a single or double leaf version, in either standard or heavy duty box section.

Constructed from high quality steel hollow box section, the robust structure of the PF5700 means it is ideally employed in unmanned

areas where there is a requirement for low volume traffic control.

This durable gate can be locked in either the open or closed position via an additional latch post or padlock respectively, providing excellent security to any area when required.

For heavy duty versions & bespoke designs please contact our sales office.

EVERY EFFORT HAS BEEN MADE IN PREPARATION OF THIS SHEET HOWEVER WE HOLD NO RESPONSIBILITY FOR ERRORS OR OMISSIONS.